

AND THE PROPERTY OF THE PROPER	
GENERAL	
Model	Honda GL 1800 SE Gold Wing ABS 2004
Category	Touring
ENGINE	
Туре	1832 cc, water cooled, 6 - cylinders boxer, 4-stroke
Bore x stroke (mm)	74 mm x 71 mm
Compression ratio	9.8:1
Valves	SOHC, 2 valves/cylinder
Fuel system	PGM-FI electronic fuel injection with automatic cold start system
Ignition	Computer-controlled digital with three-dimensional mapping
Power	118 hp (88 kW) @ 5500 rpm
Torque	167 Nm (123.2 ft. lbs.) @ 4000 rpm
TRANSMISSION	
Gearbox	5 speed
Final drive	Drive shaft
Starting system	Electronic
CHASSIS	
Front suspension	45mm fork with anti-dive system, 140 mm travel
Rear suspension	Pro Arm single-side swing arm with Pro-Link; electronically controlled spring preload adjustment with two memory presets, 104 mm travel
WHEELS	
Front tyre	130/70-R18 63H
Rear tyre	180/60-16
Front brakes	dual 296 mm discs with 3-piston callipers with Anti-Lock Braking System
Rear brakes	single 316 mm disc with 3-piston callipers with Anti-Lock Braking System
DIMENSIONS	
Overall length	2635 mm (103.7 inches)
Overall width	945 mm (37.2 inches)
Overall height	1455 mm (57.3 inches)
	740 mm (29.1 inches)
Wheelbase	1692 mm (66.6 inches)
Ground clearance	125 mm (4.9 inches)
Fuel capacity - reserve	25 Ltr (6.6 gallon US)
Dry weight	363 kg (800.3 pounds)
The above specifications are subject to change without notice. Trademarks and logos of third parties used in the Site are exclusive property of the respective owners.	